

SPECIFICATIONS

MATERIAL:	NYLON PA 6 or PA 66
IP RATING:	IP 68
STANDARD:	UL
FLAME RATING:	UL 94 V2 (V0 IS OPTIONAL)
TEMPERATURE:	-40°C ~ 100°C
	SHORT TIME 120°C
COLOUR:	BLACK, GREY, LIGHT GREY AND RED (STANDARD) OTHER COLOURS ARE AVAILABLE UPON REQUEST



CODE	CABLE RANGE	d	L	SPANNER SIZE		PACKING
				BODY	LOCKNUT	
PG TYPE	mm	mm	mm	mm	mm	pcs
PG7	3-6.5	12.5	8.0	15.5	19.5	50
PG9	4-8	15.0	8.0	18.5	21.0	50
PG11	5-10	18.4	8.0	21.5	24.0	50
PG13.5	6-12	20.4	9.0	24.0	27.0	50
PG16	10-14	22.5	10.0	26.0	29.5	50
PG21	13-18	28.4	11.0	32.0	35.0	50
PG29	18-25	37.0	11.0	41.0	46.0	10
PG36	22-32	47.0	15.5	51.0	58.5	5
PG42	32-38	54.0	16.0	60.0	63.5	5
PG48	37-44	59.3	15.5	62.0	69.0	5