

Reversible Air Screwdriver

Ideal for nut tightening work of sheet metal and vehicle

Reversible Air Screwdriver

Ideal for nut tightening work of sheet metal and vehicle

1510



1/4" Reversible
Straight Air Screwdriver

Free Speed	11,000 RPM
Clutch	Double Hammer
Max. Torque	7-30Ft-lb(9-41N-m)
Bolt Capacity	3/16" (5mm)
Ave. Air Consumption	1.2CFM(34.0 L/min)
Length	187mm (7.4in.)
Net Weight	0.8kgs[1.8lbs]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

1810



1/4" Reversible
Straight Air Screwdriver

Free Speed	9,000 RPM
Clutch	Double Hammer
Max. Torque	12-45Ft-lb(16-61N-m)
Bolt Capacity	1/4"-5/16" (6-8mm)
Ave. Air Consumption	1.5CFM(42.5 L/min)
Length	215mm (8.5in.)
Net Weight	1.1kgs[2.4lbs]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

1520



1/4" Reversible
Angle Air Screwdriver

Free Speed	9,000 RPM
Clutch	Double Hammer
Max. Torque	7-30Ft-lb(9-41N-m)
Bolt Capacity	3/16" (5mm)
Ave. Air Consumption	1.2CFM(34.0 L/min)
Length	193mm (7.6in.)
Net Weight	1.1kgs[2.4lbs]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

1820



1/4" Reversible
Angle Air Screwdriver

Free Speed	7,200 RPM
Clutch	Double Hammer
Max. Torque	9-45Ft-lb(12-61N-m)
Bolt Capacity	1/4"-5/16" (6-8mm)
Ave. Air Consumption	1.2CFM(34.0 L/min)
Length	275mm (11.0in.)
Net Weight	1.5kgs[3.3lbs]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

1811



1/4" Reversible
Straight Air Screwdriver

Free Speed	9,500 RPM
Clutch	Double Hammer
Max. Torque	12-45Ft-lb(16-61N-m)
Bolt Capacity	1/4"- 5/16" (6-8mm)
Ave. Air Consumption	1.5CFM(42.5 L/min)
Length	205mm (8.1in.)
Net Weight	1kgs[2.2lbs]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

1910



1/4" Reversible
Straight Air Screwdriver

Free Speed	10,000 RPM
Clutch	Pinless Hammer
Max. Torque	16-52Ft-lb(21-70N-m)
Bolt Capacity	1/4"- 11/32" (6-9mm)
Ave. Air Consumption	1.5CFM(42.5 L/min)
Length	230mm (9.1in.)
Net Weight	1.1kgs[2.4lbs]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

1532



1/4" Reversible Air Screwdriver

Free Speed	12,000 RPM
Clutch	Double Hammer
Max. Torque	7-30Ft-lb(9-41N-m)
Bolt Capacity	5/32-3/16" (4-5mm)
Ave. Air Consumption	1.2CFM(34.0 L/min)
Length	140mm (5.5in.)
Net Weight	1kgs[2.2lbs]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]

1832



1/4" Reversible Air Screwdriver

Free Speed	10,000 RPM
Clutch	Double Hammer
Max. Torque	12-45Ft-lb(16-61N-m)
Bolt Capacity	1/4"-5/16" (6-8mm)
Ave. Air Consumption	1.5CFM(42.5 L/min)
Length	180mm (7.1in.)
Net Weight	1.2kgs[2.6lbs]
Air Inlet	1/4"
Air Pressure	90PSI [6.3kg/cm ²]